



# Multi plank floors

The most common floor boards are the so-called multi planks. These consist of birch plywood backing bonded to solid top layer of about 5 mm thick. The total thickness of the floor planks is, therefore, about 17-18mm. These multi planks can be glued directly and completely to the existing floor. This ensures a stable floor as well as optimal efficiency of any floor heating.

Our reclaimed oak floors are produced according to the customer's wishes, so you have a say in the final appearance of the floor. Our floors are produced in 4 standard widths and in ranges between 1500 and 3000mm. We can also supply these floors with FSC-certification.

## Dimensions & stock

Length	: 80-250 cm
Width	: 17-19-21-23 cm 4 recurring widths, to be determined
Thickness	: 17-20 mm 12mm backing +5/6mm veneer top layer
Stock	: No (customization)
Price	: upon request

## Opening hours

Mo/tu/we open by appointment.
Thursday 8:00 – 17:00hour
Thursday 18:30 – 20:00 (by appointment)
Friday 8:00 – 17:00hour
Saturday 9:00 – 16:00hour



**Historisch Hout**  
Bloeme weide 6  
7448 PX Haarle  
Nederland

Phone: +31 (0)548-549785  
KVK : Zwolle 65437438  
VAT: NL219469131B01  
M: info@historischhout.nl

**Our prices include VAT, unless stated otherwise. No rights can be derived from this price list. Our general terms and conditions apply to our price lists, which can be downloaded from our website and are filed with the Chamber of Commerce.**